





- (51) International Patent Classification⁷: **G06K 19/00**,
17/00, B65G 61/00, H04B 1/59, 5/02
- (21) International Application Number:
PCT/JP2005/007113
- (22) International Filing Date: 6 April 2005 (06.04.2005)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
2004-115225 9 April 2004 (09.04.2004) JP
- (71) Applicant (for all designated States except US): SEMI-
CONDUCTOR ENERGY LABORATORY CO., LTD.
[JP/JP]; 398, Hase, Atsugi-shi, Kanagawa 243-0036 (JP).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): ARAI, Yasuyuki
[JP/JP]; c/o SEMICONDUCTOR ENERGY LABORA-
TORY CO., LTD., 398, Hase, Atsugi-shi, Kanagawa,

2430036 (JP). AKIBA, Mai [JP/JP]; c/o SEMICONDUCTOR ENERGY LABORATORY CO., LTD., 398, Hase, Atsugi-shi, Kanagawa, 2430036 (JP). TACHIMURA, Yuko [JP/JP]; c/o SEMICONDUCTOR ENERGY LABORATORY CO., LTD., 398, Hase, Atsugi-shi, Kanagawa, 2430036 (JP). KANNO, Yohei [JP/JP]; c/o SEMICONDUCTOR ENERGY LABORATORY CO., LTD., 398, Hase, Atsugi-shi, Kanagawa, 2430036 (JP).

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GI, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SI, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

- (54) Title: PRODUCT MANAGEMENT SYSTEM



(57) Abstract: When a product attached with an ID tag is placed inside a package body, there is a risk that communication with an ID tag using a reader/writer is blocked. Then, it is difficult to manage products in a distribution process of products, which leads to lose convenience of ID tags. One feature of the present invention is a product management system that includes a package body for packing a product attached with an ID tag, and a reader/writer. The ID tag includes a thin film integrated circuit portion and an antenna, the package body includes a resonance circuit portion having an antenna coil and a capacitor, and the resonance circuit portion can communicate with the reader/writer and the ID tag. Accordingly, the stability of communication between an ID tag attached to a product and an R/W can be secured, and management of products can be conducted simply and efficiently, even if a product is packed by a package body.



(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— with international search report